



TM

# JUPITER PETROTEC PRODUCTS

(Mfgs.of: Automotive, Industrial and Speciality Products & Lube Additives)

Mktg. & Admn.Off. : 24/27, Danasekaran Street, Kodambakkam, Chennai - 24.

Phone : 044-24848885. Telefax : 044-23722574. Website : [www.jupitolubricants.com](http://www.jupitolubricants.com)

Email : [jupitol\\_lubricants@vsnl.net](mailto:jupitol_lubricants@vsnl.net)

## JUPITOL Two Stroke Engine Oil (2T – Power Stroke)

Product Category	Automotive
Serial No	015
Date	01/04/2003

### Product Description

JUPITOL 2T Engine Oil (2T-Power Stroke) is a special lubricating oil developed to meet the lubrication requirements of high performance two stroke motor bikes, scooters and other two stroke engine vehicles.

This oil is formulated from the hydro-cracked, high quality HVI base oils, additives and a solvent to facilitate easy mixing with fuel with low smoke emission norms.

### Features

- Enables easy start
- Low smoke emission with Optimum lubricity
- Better burning characteristics

### Specification Level

- JASO-FC
- Exceeds API TC specification.

### Typical Characteristics

S.No	Test	UOM	Test Method	Specification of 2T Engine Oil (2T Power Stroke)
1	Appearance	NA	Visual	Bright Green Fluid
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms / cc	ASTM D 1298	0.887 (T)
4	Kin. Viscosity @ 100°C	cSt.	ASTM D 445 / IP 71	7.80 (T)
5	Kin. Viscosity @ 40°C	cSt.	ASTM D 445/ IP 71	58 (T)
6	Total Base No	mg.KOH /gm	ASTM D 2896	1.2
7	Flash Point (COC)	°C	ASTM D 92	80 (Min)
8	% Sulphated Ash	%	ASTM D 874	0.15 (Typical)

NA implies "NOT APPLICABLE"

The values mentioned above are subject to change due to continuous R & D.

Pack Sizes Sold: 210 Ltrs. packed MS Barrel / 20 ltrs packed Plastic/MS drum.