

JUPITOL

Industrial Process Oil
(IPO 02-03)

Product Category	Industrial
Serial No	050
Date	01/02/2003

Typical Characteristics

S.No	Test	UOM	Test Method	Specification
1	Appearance	NA	Visual	Clear transparent liquid without foreign particles.
2	Colour	ASTM Rating	ASTM D 1500	L0.5
3	Clarity	NA	Visual	Clear
4	Density @ 29.5°C	Gms/ cc	ASTM D 1298	0.758 (Typical)
5	Refractive Index	NA	ASTM D 1747-83	1.4280 (Typical)
6	Kinematic Viscosity @ 40°C	cSt.	ASTM D 445/ IP 71	2.2 to 2.8
7	Flash Point (PMCC)	°C	ASTM D 93	95 to 105
8	Sulphur Content	ppm	ASTM D 129	< 1.0

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continued R & D.

Packs Sold:- The above product is available in 210 Ltrs. Barrel and 20 Ltrs. Mini-drum.

=====



TM

JUPITER PETROTEC PRODUCTS

(Mfgs.of: Automotive, Industrial and Speciality Products & Lube Additives)

Mktg. & Admn.Off. : 24/27, Danasekaran Street, Kodambakkam, Chennai - 24.

Phone : 044-24848885. Telefax : 044-23722574. Website : www.jupitollubricants.com

Email : jupitol_lubricants@vsnl.net

For further details please contact :- Jupiter Petrotec Products

Factory :- 241, Vanagaram Road, Athipet, Chennai – 600 058. Ph.No.:- 26242146

JUPITOL
Industrial Process Oil
(IPO 02-03)

Product Category	Industrial
Serial No	050
Date	02/12/2004

Jupitol Industrial Process Oils are blended non-additivated, homogeneous, clear lube base oils meant for industrial processing applications and for manufacturing of lubes, thickeners, printing inks, agarbathis and allied products.

Normally the Jupitol Process Oils are customer specific products possessing generally the following properties.

Typical Characteristics

S.No	Test	UOM	Test Method	Specification
1	Appearance	NA	Visual	Bright, Clear & Transparent Liquid
2	Colour	ASTM Rating	ASTM D 1500	L0.5
3	Clarity	NA	Visual	Clear
4	Density @ 29.5°C	gms/cc	ASTM D 1298	0.758 (Typical)
5	Refractive Index	NA	ASTM D 1747	1.4280 (Typical)
6	Kin. Viscosity @ 40°C	cSt.	ASTM D 445/ IP 71	2.2 to 2.8
7	Flash Point (PMCC)	°C	ASTM D 93	95 to 105
8	Sulphur Content	ppm	ASTM D 129	< 0.5

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change from batch to batch and due to Variables in the inputs of the blends and the variation will be within the tolerance of max of 1%

Packs Sold:- The above product is available in 210 Ltrs. Barrel.

Commercial Offer:

- Basic Rate Rs.40-00 per Ltr. + ED @ 9.6% + Cess on ED @ 2% + Sales Tax @ 3.15% against Form XVII
- Delivery : Ex-Factory immediate against Purchase Order and Payment by Pay-order / Local Cheque.

JUPITOL Industrial Process Oil (IPO 12-15)
--

Product Category	Industrial
Serial No	051
Date	02/12/2004

Jupitol Industrial Process Oils are blended non-additivated, homogeneous, clear lube base oils meant for industrial processing applications and for manufacturing of lubes, thickeners, printing inks, agarbathis and allied products.

Normally the Jupitol Process Oils are customer specific products possessing generally the following properties.

Typical Characteristics

S.No	Test	UOM	Test Method	Specification
1	Appearance	NA	Visual	Bright, Clear & Transparent Liquid
2	Colour	ASTM Rating	ASTM D 1500	L1.5
3	Clarity	NA	Visual	Clear
4	Density @ 29.5°C	gms/cc	ASTM D 1298	0.845 – 0.855
5	Refractive Index	NA	ASTM D 1747	1.4280 – 1.4580
6	Kin. Viscosity @ 40°C	cSt.	ASTM D 445/ IP 71	11.80 to 15.50
7	Flash Point (PMCC)	°C	ASTM D 93	155 to 175
8	Sulphur Content	ppm	ASTM D 129	< 0.5

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change from batch to batch and due to Variables in the inputs of the blends and the variation will be within the tolerance of max of 1%

Packs Sold:- The above product is available in 210 Ltrs. Barrel.

Commercial Offer:



TM

JUPITER PETROTEC PRODUCTS

(Mfgs.of: Automotive, Industrial and Speciality Products & Lube Additives)

Mktg. & Admn.Off. : 24/27, Danasekaran Street, Kodambakkam, Chennai - 24.

Phone : 044-24848885. Telefax : 044-23722574. Website : www.jupitolubricants.com

Email : jupitol_lubricants@vsnl.net

-
- Basic Rate Rs. 32-50 per ltr. + ED @ 9.6% + Cess on ED @ 2% + Sales Tax @ 3.15% against Form XVII
 - Delivery : Ex-Factory immediate against Purchase Order and Payment by Pay-order / Local Cheque

Factory :- 241, Vanagaram Road, Athipet, Chennai – 600 058. Ph.No.:- 26242146 (Cell : 9840731961)