

Product Data Sheet

JUPITOL – CP 15

Product Category	Industrial Speciality
Serial No	012
Date	23/09/2004

Product Description:

Jupitol CP-15 is a multi-purpose tacky black coloured, thixotropic rust preventive concentrate containing permanent film forming, anti-rust and easy drying vegetable base additive components. This is applied on the metal surfaces either by dipping or by brushing or by spraying with suitable dilution proposition with mineral turpentine oil or Kerosene or any other solvent medium as per customers' choice/requirement.

Applications:

- Recommended for all Mild steel surfaces waiting for further finishing of the job on the shop-floor or awaiting for outside finishing or export clearance in the ports before despatch.

Features:

- High level rust preventive performance in very humid seashore atmosphere.
- High degree of protection against rusting and corrosion with enhanced resistance to oxidation in extended hours`
- Long duration of rust protection

Typical Characteristics:

S.No.	Test	Test Method	Results
1	Colour	Visual	Black Coloured
2	Fineness	By feel	Smooth & tacky
3	Structure	Visual	Homogeneous
4	Flash Point in °C	ASTM D 92	80°C
5	Base Oil Kin. Viscosity @ 40°C after solvent extraction	ASTM D 445	5.5 cSt

JUPITOL
Fire Resistant Hydraulic Fluids
(FRHF WG-32, WG-46 & WG-68)

Product Category	Industrial Speciality
Serial No	017
Date	01/10/2004

Product Description

JUPITOL FRHF (WG) is water glycol based Fire Resistant Hydraulic Fluid with high viscosity index fortified with anti-wear, anti-corrosion and anti-foam additives. The combination of polyglycol thickeners, anti-wear and anti-corrosion additives gives Jupitol FRHF (WG) lubricating property with other qualities like resistance to corrosion, extended equipment life, optimum performance at low temperatures. They are recommended for precision industrial equipments.

Typical Characteristics

S.No	Test	UOM	Test Method	Fire Resistant Hydraulic Fluid (WG Type)		
				FRHF WG 32	FRHF WG 46	FRHF WG 68
1	Appearance (Max.)	NA	Visual	Transparent Liquid		
2	Clarity	NA	Visual	Clear and Bright		
3	Kinematic Viscosity@ 40°C	cSt.	ASTM D-445	28.5 – 32.5	41.8 – 50.5	62.5 – 72.5
4	Viscosity Index	NA	ASTM D-2270	+ 150	+ 150	+ 150
5	Water Content	%	ASTM D-1744	35 - 40	35 - 40	35 - 40
6	Auto-ignition Temperature (Min.)	°C	ASTM D-92	462	462	468

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continuous R & D.

Packs Sold:- The above product is available in 210 Ltrs. Barrel



TM

JUPITER PETROTEC PRODUCTS

(Mfgs.of: Automotive, Industrial and Speciality Products & Lube Additives)

Mktg. & Admn.Off. : 24/27, Danasekaran Street, Kodambakkam, Chennai - 24.

Phone : 044-24848885. Telefax : 044-23722574. Website : www.jupitolubricants.com

Email : jupitol_lubricants@vsnl.net
