



TM

JUPITER PETROTEC PRODUCTS

(Mfgs.of: Automotive, Industrial and Speciality Products & Lube Additives)

Mktg. & Admn.Off. : 24/27, Danasekaran Street, Kodambakkam, Chennai - 24.

Phone : 044-24848885. Telefax : 044-23722574. Website : www.jupitolubricants.com

Email : jupitol_lubricants@vsnl.net

JUPITOL
Sugar Mill Compound (LVC-100,MVC-250 & HVC-500)

Product Category	Industrial
Serial No	032
Date	01/04/2003

Product Description:-

Jupitol Sugar Mill Compound (LVC-100, MVC-250 & HVC-500) are high viscous residual compounds which adhere tenaciously to clean metal surfaces. They are fortified with special tackiness agents and have excellent film strength to withstand the high pressure normally encountered in heavily loaded open gears. They are available in different viscosities conforming to BIS: 9554-88.

Recommendations:-

- Conventional open gears which are hand lubricated by brush or swab.

Typical Characteristics:-

S.No.	Test	UOM	Test Method	Specification of Sugar Mill Compound		
				LVC-100	MVC-250	HVC-500
1	Colour	-	Visual	Black	Black	Black
2	Kinematic Viscosity @ 100°C	cSt.	ASTM D 445 / IP 71	80 to 120	195 to 305	440 to 660
3	Flash Point (COC)	°C	ASTM D 92	225	225	225
4	Copper Corrosion@ 100°C, Max.	NA	ASTM D 130	-ve	-ve	-ve
5	Inorganic Acidity	mgm. KOH per gm.		Nil	Nil	Nil
6	Water Content,by Mass	%		1.0	1.0	1.0

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continued R & D.

Packs Sold:- The above product is available in 210 Ltrs. Barrel and 20 Ltrs. Mini-drum.